



# SCANMEG

## Type HD



### Light-curtain scanner

- Simple alignment
- Watertight casing
- Digital display of results
- Programmable metric or imperial unit
- LED detection status for each cell
- Opto-isolated outputs: analog and serial
- Parameters setting via remote control

Model	
HD	LD
Length	
10 in.	250 mm
20 in.	500 mm
30 in.	750 mm
⋮	⋮
⋮	⋮
140 in.	3500 mm
150 in.	3750 mm
160 in.	4000 mm

1 mm Accuracy 0.040 in.

### Model

HD  
LD

### Length

10 in.	250 mm
20 in.	500 mm
30 in.	750 mm
⋮	⋮
⋮	⋮
140 in.	3500 mm
150 in.	3750 mm
160 in.	4000 mm

### Accuracy

HD:	0.040 in.	1 mm
LD:	0.160 in.	4 mm

### Power Supply

12 to 24 Volts DC

### Operating Temperature

Min.:	-40°F	-40°C
Max.:	120°F	50°C

### Current consumption

HD500:	675 mA
LD500:	650 mA

### Detection range

HD:	16 ft	5 m
LD:	16 ft	5 m

### Maximum Scan rate

<u>(scans/sec.)</u>	
HD500:	802
LD500:	953

### Output interface

Analog 4-20 ma (2x)  
Serial link RS-422

### **North America** *(Western Representative)*

John Wilby  
10972 Swan Crescent  
Surrey, BC, V3R 5B6  
Tel.: 604-582-2157  
Fax: 604-582-2105  
Cell.: 604-290-6595  
Email: jwilby@scanmeg.com

The Type HD increases your productivity by measuring the dimension and position of an object with highest accuracy and speed unheard of until now.

With two analog outputs built into our different models, the interface with a PLC (programmable logic controller) has never been so simple. The first output gives the dimension and the second one the position of the object.

## Model HD

The type HD scanner detects and measures objects with an unsurpassed 1 mm (0.040 inch) accuracy for a light-curtain scanner. Standard features include: Two analog 4-20 mA outputs, one serial link, completely sealed unit, military connectors, rugged enclosure designed for industrial environment and can operate up to a 10 degree misalignment between Emitter and Receiver.

## Model LD

LD model has every HD model features but accuracy is 4 mm (0.160 inch). This allows one to select this scanner for a lower price when accuracy is not a major issue.

- Two operation modes
- Five scanning modes
- Digital display of results
- Visual status of each cell
- Remote control
- Conveyor calibration
- One RS-422 serial link
- Two analog 4-20mA outputs
- Two communication protocols
- Programmable minimum detectable object

### Remote control



All parameters can be visualized or modified with a standard infrared remote control. Commands settings and diagnostics procedures are also accessible with the remote control. Interface, computer and serial link are no longer mandatory. All procedures can now be done at the scanner level.



**3517 Boul. Grande Allee,  
Boisbriand, QC  
Canada, J7H 1H5**

**Tel.: (450) 419-4555  
Fax: (450) 419-4542  
Email: sales@scanmeg.com  
Web: www.scanmeg.com**

The Ultimate Sensor Company

### **Europe**

82 Route de Séchex  
F-74200 ANTHY-SUR-LEMAN  
France  
Tel. / Fax: +33 (0)4 50 17 25 33  
Cell: +33 (0)6 31 54 38 06  
Email: europe@scanmeg.com

### **Japan**

532 Ohyanagi Minami Shimada-City  
Shizuoka-Prefecture  
Japan, 427-0102  
Tel.: +81-547-38-3211  
Fax: +81-547-38-2122  
Email: info@hirotacorp.jp